Mind Map-4

⊗ Cross, if magnetic field is directed perpendicular and into the plane of the paper

· Dot, if magnetic field is directed perpendicular and out of the plane of the paper.

Galvanometer to ammeter conversion: Low resistance or shunt connected in parallel $S = \left(\frac{I_g}{I - I_g}\right)G$

Reading of ammeter is always less than actual current in the circuit.

Galvanometer to voltmeter conversion: High resistance

Greater the resistance of voltmeter, more accurate its reading.

Magnetic field due to a current carrying wire at a point which lies at a perpendicular distance

r from the wire $B = \frac{\mu_0}{4\pi} \cdot \frac{1}{r} (\sin \phi_1 + \sin \phi_2)$

or, $B = \frac{\mu_0}{4\pi} \cdot \frac{1}{r} (\cos \alpha - \cos \beta)$ For a wire of finite length Magnetic field at a point which lies on perpendicular bisector of finite length wire $B = \frac{\mu_0}{4\pi} \cdot \frac{1}{r} (2\sin\phi)$

For a wire of infinite length When the linear conductor is of infinite length and the

mean conductor is of infinite length and the point lies near the centre of the conductor. $B = \frac{\mu_0}{4\pi} \frac{i}{r} (\sin 90^\circ + \sin 90^\circ) = \frac{\mu_0}{4\pi r}$ For a wire of semi-infinite length When the linear search are the first linear tensor and the linear search are the search are the search and the linear search are the searc

linear conductor is of infinite length and the point lies near the end

B =
$$\frac{\mu_0}{4\pi} \cdot \frac{i}{r} (\sin 90^\circ + \sin 0^\circ) = \frac{\mu_0 i}{4\pi r}$$

For axial position of wire When point lies

on axial position of current carrying conductor then magnetic field B = 0

Magnetic field due to a straight current carrying conductor of infinite length $B = \frac{\mu_0 I}{\mu_0 I}$

Biot-Savart's law Magnetic field due to current carrying element, $dB = \frac{\mu_0}{4\pi} \frac{Idl \sin \theta_n}{r^2}$ $4\pi r^2$ It is an imverse-square law and is the magnetic analogue of coulomb's law

Magnetic field due to a current carrying circular loop

On the axis of circular loop $B = \mu_0 N Ia^3$ $2(r^2+a^2)^{3/2}$ If a \gg r, B = ℓ $\frac{\mu_0}{4\pi} \cdot \frac{2NiA}{a^3}$

At the centre of circular loop $B = \frac{\mu NI}{\mu NI}$ Magnetic field due to circular current carrying are $B = \frac{\mu_0 I}{2r}$

Magnetic field due to a solenoid. Inside a long solenoid $B = \mu_0 nI$ At a point on one end $B - \frac{\mu_0 nI}{\mu_0}$ n - number of turns per unit length

Ampere's circuital law $\oint Bdl = \mu_0 \Sigma i$ Absolute permeability of air or vacuum, of all of vacc. $\mu_0 = 4\pi \times 10^{-7} \frac{Wb}{Amp - metre}$

Magnetic field due to a **toroid** $B = \mu_0 nI; \quad n = \frac{N}{2\pi r}$

Magnetic field due to a cylindrical wire. **Outside the cylinder** Magnetic field $B_{out} = \frac{\mu_0 t}{2\pi r}$ and $B_{surface} = \frac{\mu_0 t}{2\pi r}$.

Inside the hollow cylinder Magnetic field inside the hollow cylinder is zero.

Direction of magnetic field-Depends upon the direction of current. Right hand thumb rule-Thumb points in the direction of current, curling of fingers represents direction of magnetic field.

Magnetic field space in the surrounding of a magnet or any current carrying conductor in which its magnetic influence can be experienced

Moving Charges And Magnetism

Magnetic field within the solenoid is uniform and parallel to the axis of solenoid.

Amperic law is analogous to Gauss's

law $\oint \vec{E} \cdot d\vec{s} = \frac{q}{r}$

This law is valid for symmetrical current distributions and is based on the principle of electromagnetism

Toroid is like an endless cylindrical solenoid. Number of turns per unit

length $n = \frac{N}{2\pi r}$

Inside the solid cylinder

Magnetic field $B = \frac{\mu_0}{2\pi} \cdot \frac{ir}{R^2}$ Inside the thick portion of hollow cylinder:

 $B = \frac{\mu_0 i}{2\pi r} \cdot \frac{(r^2 - R_1^2)}{2\pi r (R_2^2 - R_1^2)}$

Motion of a charged particle in a uniform magnetic field follows a circular path, radius $MV \sin \theta$ Bq

Force on a conductor carrying current in a uniform magnetic field, $F = I B l \sin \theta$ $F = I (B \times l)$

Force between two parallel current carrying conductors $F = \frac{\mu_0}{4\pi} \cdot \frac{2I_1I_2}{r} \times I$

If two charges q₁, q₂ are moving with velocities v₁ and v₂ and at any instant distance between then is 'r'

 $F_{\text{magnetic}} = \frac{\mu_0}{4\pi} \frac{q_1 q_2 \nu_1 \nu_2}{r^2}$ For charges moving with

same velocity $F_{\text{magnetic}} \leq F_{\text{electrostatic}}$ Force acting on a charged particle moving in a uniform magnetic field F = aVB $\sin \theta = q(V \times B)$

Lorentz force $F = q[\vec{E} + \vec{V} \times \vec{B}]$ Electric force, $\vec{F}_e = q\vec{E}$ Magnetic force,

all connect \vec{r}_{magnene} $\vec{F}_{e}, = q\vec{E} \Rightarrow \vec{a} = \frac{\vec{F}}{m} = \frac{q\vec{E}}{m}$ • When \vec{V}, \vec{E} and \vec{B} are mutually perpendicular $\vec{F}_m = q(\vec{v} \times \vec{B})$ $\vec{F} = \vec{F}_o \Rightarrow \vec{F}_m = 0$ $\Rightarrow a = \frac{\vec{F}}{m} = 0$

Direction of force If two conductors carry current in same direction, force between them is attractive and if carry currents in opposite direction force between them is repnisive

> Torque experienced by a current carrying loop in a uniform magnetic field $\vec{T} = MB \sin \theta \hat{n}$

- **Torque** experienced is zero when $\theta = 0$ i.e. plane of the coil is perpendicular to the field.
- Torque is maximum when $\theta = 90^{\circ}$ i.e., plane of the coil is parallel to the field, $T_{max} = NBiA$
- Work done, $W = MB(1 \cos \theta)$

$$\begin{array}{l} W_{max},\,if\;\theta=180^{\circ}\\ W_{max}=2MB \end{array}$$

· Potential energy. $U = -MB\cos\theta \Rightarrow U = -\vec{M}.\vec{B}$ Zero force i.e., F = 0 on a charged particle, if field $\vec{B} = 0$ charge q = 0charge is at rest, v = 0when $\theta = \theta^{\circ}$ or 180°

• When \vec{V} , \vec{E} and \vec{B} are all collinear $F_{\text{magnetic}} = 0$

Trajectory of a particle is a circle if particle velocity \vec{v} perpendicular to \vec{B} i.e., $\theta = 90^{\circ}$ and radius of path,

parallel to \vec{R}

Trajectory of a particle is a

of a particle moving with

velocity v parallel or anti-

i.e., $\theta = 0$ or $\theta = 180^{\circ}$

straight, line, if the direction

 $r-\frac{mV}{qB}-\frac{1}{B}\sqrt{\frac{2mV}{q}}$

Trajectory of a particle is helical if a charged particle is moving at an angle to the field other than 0°, 90°, 180° and radius of path $r = \frac{m(V \sin \theta)}{m(V \sin \theta)}$ qB

Cyclotron.

A device used to accelerate positively charged particles like α-particles, deuterons, etc. to acquire sufficient energy to carry out nuclear disintegration.

• Cyclorton frequency $v = \frac{qB}{2\pi m}$

Cyclotron frequency also known as magnetic resonance frequency

- Time period, $T = \frac{2\pi m}{qB}$
- Maximum energy gained by charged particle

$$E_{\text{max}} = \left(\frac{q^2 B^2}{2m}\right) r^2$$